

Universal PCI智能多串口卡

参数/ 型号	串口 数量	串口界面	PCI-X 总线	系统 结构	P640NU 智能串口卡	A640 电缆线	NF116 连接盒	NF216 连接盒	NF316 连接盒	只需要使用 一个IRQ
P1016	16	RS232	√		1块	1条	1个			√
P1032	32	RS232	√		1块	√	2个			√
P1048	48	RS232	√		1块	√	3个			√
P1064	64	RS232	√		1块	√	4个			√
P2016	16	RS422/485	√		1块	√		1个		√
P2032	32	RS422/485	√		1块	√		2个		√
P2048	48	RS422/485	√		1块	√		3个		√
P2064	64	RS422/485	√		1块	√		4个		√
P3016	16	RS232/422/485	√		1块	√			1个	√
P3032	32	RS232/422/485	√		1块	√			2个	√
P3048	48	RS232/422/485	√		1块	√			3个	√
P3064	64	RS232/422/485	√		1块	√			4个	√
P1232	32	16个RS232	√		1块	√	1个	1个		√
		16个RS422/485								
P1332	32	16个RS232	√		1块	√	1个		1个	√
		16个RS232/422/485								
P2332	32	16个RS422/485	√		1块	√		1个	1个	√
		16个RS232/422/485								

Universal PCI地电位隔离智能多串口卡

参数/ 型号	串口 数量	串口界面	PCI-X 总线	系统 结构	P640NU 智能串口卡	A640 电缆线	IF108 连接盒	IF208 连接盒	IF308 连接盒	只需要使用 一个IRQ
UP1008I	8	RS232	√		1块	1条	1个			√
UP1016I	16	RS232	√		1块	√	2个			√
UP1024I	24	RS232	√		1块	√	3个			√
UP1032I	32	RS232	√		1块	√	4个			√
UP2008I	8	RS422/485	√		1块	√		1个		√
UP2016I	16	RS422/485	√		1块	√		2个		√
UP2024I	24	RS422/485	√		1块	√		3个		√
UP2032I	32	RS422/485	√		1块	√		4个		√
UP3008I	8	RS232/422/485	√		1块	√			1个	√
UP3016I	16	RS232/422/485	√		1块	√			2个	√
UP3024I	24	RS232/422/485	√		1块	√			3个	√
UP3032I	32	RS232/422/485	√		1块	√			4个	√
UP1216I	16	16个RS232	√		1块	√	1个	1个		√
		16个RS422/485								
UP1316I	16	16个RS232	√		1块	√	1个		1个	√
		16个RS232/422/485								
UP2316I	16	16个RS422/485	√		1块	√		1个	1个	√
		16个RS232/422/485								

PCIe智能多串口卡

参数/型号	串口数量	串口界面	PCI Express 总线	系统结构	A320智能串口卡	A640 电缆线	NF116 连接盒	NF216 连接盒	NF316 连接盒	只需要使用一个IRQ
A1016	16	RS232	√		1块	1条	1个			√
A1032	32	RS232	√		1块	√	2个			√
A1048	48	RS232	√		1块	√	3个			√
A1064	64	RS232	√		1块	√	4个			√
A2016	16	RS422/485	√		1块	√		1个		√
A2032	32	RS422/485	√		1块	√		2个		√
A2048	48	RS422/485	√		1块	√		3个		√
A2064	64	RS422/485	√		1块	√		4个		√
A3016	16	RS232/422/485	√		1块	√			1个	√
A3032	32	RS232/422/485	√		1块	√			2个	√
A3048	48	RS232/422/485	√		1块	√			3个	√
A3064	64	RS232/422/485	√		1块	√			4个	√
A1232	32	16个RS232 16个RS422/485	√		1块	√	1个	1个		√
A1332	32	16个RS232 16个RS232/422/485	√		1块	√	1个		1个	√
A2332	32	16个RS422/485 16个RS232/422/485	√		1块	√		1个	1个	√

PCIe地电位隔离智能多串口卡

参数/型号	串口数量	串口界面	PCI Express 总线	系统结构	A320智能串口卡	A640 电缆线	IF108 连接盒	IF208 连接盒	IF308 连接盒	只需要使用一个IRQ
A1008I	8	RS232	√		1块	1条	1个			√
A1016I	16	RS232	√		1块	√	2个			√
A1024I	24	RS232	√		1块	√	3个			√
A1032I	32	RS232	√		1块	√	4个			√
A2008I	8	RS422/485	√		1块	√		1个		√
A2016I	16	RS422/485	√		1块	√		2个		√
A2024I	24	RS422/485	√		1块	√		3个		√
A2032I	32	RS422/485	√		1块	√		4个		√
A3008I	8	RS232/422/485	√		1块	√			1个	√
A3016I	16	RS232/422/485	√		1块	√			2个	√
A3024I	24	RS232/422/485	√		1块	√			3个	√
A3032I	32	RS232/422/485	√		1块	√			4个	√
A1216I	16	16个RS232 16个RS422/485	√		1块	√	1个	1个		√
A1316I	16	16个RS232 16个RS232/422/485	√		1块	√	1个		1个	√
A2316I	16	16个RS422/485 16个RS232/422/485	√		1块	√		1个	1个	√